https://msdsreport.com/msds/BDHCM

AMOCO 300 MOTOR OILS

repor

MSDS Number

BDHCM

National Stock Number

9150-00-186-6683

Product Name

AMOCO 300 MOTOR OILS

Manufacturer

AMOCO OIL COMPANY

Product Identification

Product ID:AMOCO 300 MOTOR OILS MSDS Date:01/01/1985 FSC:9150 NIIN:00-186-6683 MSDS Number: BDHCM

Responsible Party

AMOCO OIL COMPANY

Emergency Phone: (312)8565371

Cage: 15958

Contractor

AMOCO OIL CO

3488

HINSDALE, IL 60522-3488

US

800-652-6626

Cage: 2V812

Ingredients

PETROLEUM OILS

Fraction By Weight: UNK

ADDITIVES

Fraction By Weight: UNK

Hazards

Effects of Overexposure:EYES:MINIMALLY IRRITATING;SKIN:SLIGHTLY IRRITATING;INH:NONE;ING:PRACTICALL NONTAXIC FOR ACUTE.

First Aid

First Aid:EYES:FLUSH W/PLENTY OF H*2;SKIN:NONE REQD FOR UNUSED OIL CONTACT W/USED MOTOR OIL-WASH EXPOSED SKIN THOROUGHLY W/SOAP & WATER;INGESTION:IF A LARGE AMT IS SWALLOWED,INDUCD VOMITING MEDICAL

Fire Fighting

Flash Point:400-450F-COC Extinguishing Media:DRY CHEMICAL(B-C),CO*2, WATER FOG, FOAM Fire Fighting Procedures:NONE KNOWN Unusual Fire/Explosion Hazard:NONE

Accidental Release



Spill Release Procedures:ELIMINATE IGN SOURCES>STOP LEAK W/O RISK.USE PROTECTIVE QUIP SUCH AS GLOVES & SAFETY GLASS DURING CLEANUP SPILL;SM SPILL:ABSORB W/COMMERCIAL ABSORBENT & CONTAIN IN COVERED DRUM;LG SPILL:DIKE LIQ. PUMP INTO SALVAGE TANK.SHOVEL RESIDUE INTO COVERDDRUM

•

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:CAUTION:CONTINUOUS LONG TERM CONTCT W/USED OIL HAS CAUSED CANCER IN ANIMAL TESTS;USE WATERLESS HAND CLEANER TO REMOVE USED OIL FM SKIN.USE PROTCTV CLOTHINGS & GLOVES WHEN WORKING W/USED OILS,=

Exposure Controls

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:GENERAL (MECH)/AREA Protective Gloves:IMPERVIOUS Eye Protection:AS REQUIRED Other Protective Equipment:WEAR PROTCTV CLOTHING & IMPERVIOUS GLOVES Supplemental Safety and Health MSDS DTD NOV 1982 COVERS:SAE 10W;20-20W;30;40; & 15W-40 GRADE OIL;THIS NSN FOR MIL-L-46152B, 10W GRADE

Chemical Properties

HCC:V6 Spec Gravity:0.885 Solubility in Water:NEGLIGIBLE Appearance and Odor:PALE TO LIGHT RED COLORED OILY LIQUID

Stability

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:IGNITION SOURCES Hazardous Decomposition Products:C, CO, CO*2, VARIOUS HYDROCARBONS & THEIR DERIVATIVES

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.