
1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Borane tetrahydrofuran complex solution

Product Number : 176192

Brand : Aldrich

Supplier : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

Emergency Phone # (For both supplier and manufacturer) : (314) 776-6555

Preparation Information : Sigma-Aldrich Corporation
Product Safety - Americas Region
1-800-521-8956

2. HAZARDS IDENTIFICATION**Emergency Overview****OSHA Hazards**

Flammable liquid, Water Reactive, Harmful by ingestion., Irritant, Target Organ Effect, Carcinogen

Target Organs

Central nervous system, Liver, Kidney

GHS Classification

Flammable liquids (Category 2)

Substances, which in contact with water, emit flammable gases (Category 1)

Acute toxicity, Oral (Category 4)

Acute toxicity, Dermal (Category 5)

Skin irritation (Category 2)

Serious eye damage (Category 1)

Specific target organ toxicity - single exposure (Category 3)

GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H260

In contact with water releases flammable gases which may ignite spontaneously.

H302

Harmful if swallowed.

H313

May be harmful in contact with skin.

H315

Causes skin irritation.

H318

Causes serious eye damage.

H335

May cause respiratory irritation.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P223

Keep away from any possible contact with water, because of violent reaction and

P231 + P232 possible flash fire.
 P261 Handle under inert gas. Protect from moisture.
 P280 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P305 + P351 + P338 Wear protective gloves/ eye protection/ face protection.
 P370 + P378 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P422 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
 Store contents under inert gas.

Other hazards

May form explosive peroxides.

HMIS Classification

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical hazards: 2

NFPA Rating

Health hazard: 2
Fire: 3
Reactivity Hazard: 2
Special hazard.: W

Potential Health Effects

Inhalation May be harmful if inhaled. Causes respiratory tract irritation.
Skin Harmful if absorbed through skin. Causes skin irritation.
Eyes Causes eye irritation.
Ingestion Harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C₄H₁₁BO
 Molecular Weight : 85.94 g/mol

Component	Classification	Concentration
Tetrahydrofuran		
CAS-No. 109-99-9	Flam. Liq. 2; Eye Irrit. 2; Carc. 2; STOT SE 3; H225, H319, H335, H351, EUH019	90 - 100 %
EC-No. 203-726-8		
Index-No. 603-025-00-0		
Tetrahydrofuran-borane		
CAS-No. 14044-65-6	Flam. Liq. 2; Water-react. 1; Skin Irrit. 2; Eye Irrit. 2; H225, H260, H315, H319	5 - 10 %
EC-No. 237-881-8		

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

4. FIRST AID MEASURES

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES

Conditions of flammability

Flammable in the presence of a source of ignition when the temperature is above the flash point. May burn in presence of air, or emit a flammable gas in the presence of water or water vapour. Keep away from heat/sparks/open flame/hot surface. No smoking. Keep away from heat/sparks/open flame/hot surface/air/water. No smoking.

Suitable extinguishing media

Dry powder

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous combustion products

no data available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not flush with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Never allow product to get in contact with water during storage.

Recommended storage temperature: 2 - 8 °C

Do not allow water to enter container. Handle and store under inert gas. The pressure in sealed containers can increase under the influence of heat.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Tetrahydrofuran	109-99-9	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
Remarks	Central Nervous System impairment Upper Respiratory Tract irritation Kidney damage Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption			
		STEL	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Central Nervous System impairment Upper Respiratory Tract irritation Kidney damage Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption			
		STEL	250 ppm 735 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

		TWA	200 ppm 590 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	The value in mg/m3 is approximate.			
		TWA	200 ppm 590 mg/m3	USA. NIOSH Recommended Exposure Limits
		ST	250 ppm 735 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	200 ppm 590 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 10 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid
Colour colourless

Safety data

pH no data available
Melting point/freezing point no data available
Boiling point 65.5 - 66.5 °C (149.9 - 151.7 °F)
Flash point -17 °C (1 °F) - closed cup
Ignition temperature 103 °C (217 °F)

Auto-ignition temperature	no data available
Lower explosion limit	1.58 %(V)
Upper explosion limit	12.42 %(V)
Vapour pressure	no data available
Density	0.898 g/cm ³ at 25 °C (77 °F)
Water solubility	no data available
Partition coefficient: n-octanol/water	no data available
Relative vapour density	no data available
Odour	no data available
Odour Threshold	no data available
Evaporation rate	no data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.
Reacts violently with water.

Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Exposure to moisture.

Materials to avoid

acids, Acid chlorides, Acid anhydrides, Alcohols, Oxidizing agents, Oxygen

Hazardous decomposition products

no data available

Contains the following stabiliser(s):

Sodium borohydride (<0.019 %)

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - rat - > 500 - < 2,000 mg/kg

no data available

Inhalation LC50

no data available

Dermal LD50

no data available

Other information on acute toxicity

no data available

Skin corrosion/irritation

Skin - rabbit - Skin irritation - OECD Test Guideline 404

Serious eye damage/eye irritation

Eyes: no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

no data available

Teratogenicity

no data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

Aspiration hazard

no data available

Potential health effects

Inhalation	May be harmful if inhaled. Causes respiratory tract irritation.
Ingestion	Harmful if swallowed.
Skin	Harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.

Signs and Symptoms of Exposure

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

no data available

Additional Information

RTECS: Not available

12. ECOLOGICAL INFORMATION

Toxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

PBT and vPvB assessment

no data available

Other adverse effects

no data available

13. DISPOSAL CONSIDERATIONS

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3399 Class: 4.3 (3) Packing group: I
Proper shipping name: Organometallic substance, liquid, water-reactive, flammable (Tetrahydrofuran-borane, Tetrahydrofuran)
Reportable Quantity (RQ): 1106 lbs
Marine pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 3399 Class: 4.3 (3) Packing group: I EMS-No: F-G, S-N
Proper shipping name: ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (Tetrahydrofuran-borane, Tetrahydrofuran)
Marine pollutant: No

IATA

UN number: 3399 Class: 4.3 (3) Packing group: I
Proper shipping name: Organometallic substance, liquid, water-reactive, flammable (Tetrahydrofuran-borane, Tetrahydrofuran)

15. REGULATORY INFORMATION

OSHA Hazards

Flammable liquid, Water Reactive, Harmful by ingestion., Irritant, Target Organ Effect, Carcinogen

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Tetrahydrofuran	CAS-No. 109-99-9	Revision Date 2007-03-01
-----------------	---------------------	-----------------------------

Pennsylvania Right To Know Components

Tetrahydrofuran	CAS-No. 109-99-9	Revision Date 2007-03-01
Tetrahydrofuran-borane	14044-65-6	

New Jersey Right To Know Components

Tetrahydrofuran	CAS-No. 109-99-9	Revision Date 2007-03-01
Tetrahydrofuran-borane	14044-65-6	

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Text of H-code(s) and R-phrase(s) mentioned in Section 3

Carc.	Carcinogenicity
EUH019	May form explosive peroxides.
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure
Water-react.	Substances, which in contact with water, emit flammable gases

Further information

Copyright 2013 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.