MATERIAL SAFETY DATA SHEET HARRY J. BOSWORTH COMPANY

7227 North Hamlin Avenue Skokie, Illinois 60076-3999 Information Phone: 847.679.3400

Emergency Phone: 800.535.5053

HAZARD RATING

N 4 - EXTREME

3 - HIGH

2 - MODERATE

A 1 - SLIGHT

0 - INSIGNIFICANT



PRODUCT:

Tac Adhesive Spray

DATE PREPARED:

Hazardous Components

INGREDIENTS:

- 1.) Amide Resin Solution
- 2.) Isopropyl Alcohol
- 3.) Propellant
- 4.) Toluene

COMMON NAMES AND SYNONYMS:

- 1.) Amide Resin Solution
- 2.) Isopropanol
- 3.) Liqueified Petroleum Gas
- 4.) Methyl Benzene

PEL:

- 1.) N/A
- 2.) 400 ppm
- 3.) 1000 ppm
- 4.) 100 ppm

TLV:

- 1) 200 ppm
- 2.) 400 ppm
- 3.) 1000 ppm 4.) 100 ppm

- PERCENTAGE:
 - 1.) N/A
 - 2.) N/A
 - 3.) N/A
 - 4.) N/A

CAS NUMBER:

- 1.) 108883
- 2.) 67-63-0
- 3.) 68476-85-7
- 4.) 108-88-3

UN NUMBER:

- 1.) N/A
- 2.) 1219
- 3.) N/A
- 4.) N/A

Physical/Chemical Characteristics

BOILING POINT:

-44 to 180°F (-42 to 82°C)

Pressure in can at 70°F

(21°C) Approximately

50 p sig

SPECIFIC GRAVITY: (H20=1)

VAPOR DENSITY:

(Air = 1) 2.01

VAPOR PRESSURE:

33 mg (Hg)

EVAPORATION RATE:

(Butvi Acetate = 1) Greater than 1

APPEARANCE/ODOR:

Amber-clear liquid with characteristic

odor. Tacky

SOLUBILITY IN WATER:

slightly soluble (adhesive)

Reactivity Data

STABILITY:

stable at room temperature

CONDITIONS TO AVOID:

Keep away from heat, spark, flame and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon dioxide, carbon monoxide, and toxic gases possible if thermally decomposed

HAZARDOUS POLYMERIZATION:

Will not occur.

CONDITIONS TO AVOID:

Open flames, other ignition sources, strong oxidizing agents.

Fire and Explosion Hazard Data

FLASH POINT:

LIMITS:

-156°F (-104°) for aerosol propellant

LEL: 1.9

UEL: 9.5

EXTINGUISHING MEDIA:

Dry chemical, foam, or carbon dioxide. Water spray may be used to keep fire-exposed container cool.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapor can flow along surfaces to distant ignition sources and flash back. Prevent spreading of vapor. Spray cans may explode if heated.

Health Hazard Data

CARCINGGENICITY:

NTP

California Proposition 65 Warning: This product may contain a chemical known to the state of California to cause birth defects

N/A

IARC N/A

OSHA REGULATED

Effects and Hazards of Overexposure

(Acute and Chronic)

EFFECTS AND HAZARDS OF EYE CONTACT: May cause irritation, defatting or dermatitis

EFFECTS AND HAZARDS OF SKIN CONTACT:

Prolonged or repeated exposure may cause irritation, defatting or dermatitis

EFFECTS AND HAZARDS OF INHALATION (BREATHING): Inhalation may cause respiratory irritation, dizziness, nausea, possible unconclousness or asphyxiation.

EFFECTS AND HAZARDS OF INGESTION (SWALLOWING) May cause abdominal discomfort, nausea, vomitting, or diarrhea

OTHER REGULATORY INFORMATION:

California Proposition 65: This product may contain a chemical known to the state of California to cause birth defects.

Emergency and First Aid Procedures

TREATMENT FOR EYE CONTACT:

Wash eyes with plenty of water for at least 15 minutes. Call a physician.

TEATMENT FOR SKIN CONTACT:

Wash skin with soan and water. If irritation develops, get medical attention. Remove soaked clothing to avoid prolonged skin contact.

TREATMENT FOR INHALATION (BREATHING).

Remove to fresh air. Resuscitate if necessary or use oxygen and see physician.

TREATMENT FOR INGESTION (SWALLOWING):

Dilute by swallowing water, milk or eggwhite. Do not induce vomiting, see physician. Do not give fluids to unconcious person

Precautions for Safe Handling and Use

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Absorb material and pick up with nonsparking tools. Place in sealed containers. Ventilate area

WASTE DISPOSAL METHOD:

Abide local, state and federal laws of disposal. Use conventional solvent waste receptacle. Avoid contamination of groundwater

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool dry place. Keep tightly closed when not in use. Avoid sources of ignition, or heat. Do not store where temperature may exceed 120°F (49°C)

OTHER PRECAUTIONS

Health Index:

This product is for professional use only as stated in directions. It is the responsibility of the dentist to train personnel.

Control Measures

RESPIRATORY PROTECTION:

Use NIOSH-approved respirators in case of high vapor concentration, with organic vapor cartridge

Additional Information

This MSDS was prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29CFR 1910 1200) and is to be used only for this product. The information contained in this sheet is , to the best of our knowledge, believed to be accurate

Ratings:

Ventilation I LOCAL EXHAUST VENTILATION: As needed SPECIAL VENTILATION: As needed MECHANICAL (GENERAL) VENTILATION: None OTHER VENTILATION: Open window if necessary PROTECTION GLOVES: Use if needed, rubber or plastic gloves. EYE PROTECTION: Use if needed, safety glasses with side shields OTHER PROTECTIVE EQUIPMENT: **WORK AND HYGIENIC PRACTICES:**

SEVERE HAZARD	1
SERIOUS HAZARD	2
MODERATE HAZARD	3
SLIGHT HAZARD	4
MINIMUM HAZARD	5
Shipping Information	
REGULATED IATA:	
, N/A	
PROPER SHIPPING NAME:	
Flammable liquids NOS Class	
HAZARD CLASS:	
3	
IDENTIFICATION NUMBER:	
UN 1993	
PACKAGING GROUP:	
, III	
LABEL: Flammable Liquid	

To the best of our knowledge, the information contained herein is accurate. However, The Harry J. Bosworth company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist

Wash hands before smoking or eating