

# SAFETY DATA SHEET

## RONSON BUTANE REFILL

---

### 1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

---

**Product Name:** Ronson Butane Refill  
**Synonyms, Trade Names:** Butane Fuel 90ml to 400ml  
**Applications:** Gas lighter fuel  
**Supplier:** Ronson International Ltd.  
International House, Old Brighton Road,  
Lowfield Heath. Crawley, West Sussex. RH11 0QN  
**Emergency Telephone:** 01293 843600 (office hours only)

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

---

Ingredient Name	CAS No	Contents	Health (class)	Risk (R No.)
Butane	106 - 97 - 8	99%		

**Composition Comments** Substances indicating a hazard do so under EC Directives 88/379 & 67/548  
Aerosol classified as Flammable

---

### 3. HAZARDS IDENTIFICATION

---

**Flammable**  
Substances not indicating a health hazard may have **Occupational Exposure Limits** detailed in Section 8 of this data sheet  
Ingredients are below the levels to cause the product to be classified

---

### 4. FIRST AID MEASURES

---

**General:** Note! Keep affected person away from heat, sparks and flames!  
**Eyes:** Promptly wash eyes with water while lifting the eyelids. Get medical attention immediately. Continue to rinse. Burns should be flushed with water to normalise temperature. Cover eyes with sterile dressing. Do NOT apply ointments or powder.  
**Skin:** Remove affected person from source of contamination. Promptly stop exposure and get medical attention if frostbite has occurred. Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water.  
**Inhalation:** Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get prompt medical attention  
**Ingestion:** NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS.  
DO NOT induce vomiting Get medical attention immediately.

---

### 5. FIRE FIGHTING MEASURES

---

**Extinguishing Media** Stop flow of material to fire. Fire can be extinguished using foam, dry chemicals, and sand dolomite etc.  
**Special Fire Fighting Procedures** Use water to keep fire exposed cool and disperse vapours. Cool containers exposed to flames with water from side until well after fire is out. Move container from fire area if it can be done without risk.

# SAFETY DATA SHEET

## RONSON BUTANE REFILL

### Unusual Fire & Explosion Hazards

Extremely flammable. May explode in a fire. May travel considerable distance to source of ignition and flashback.

### Hazardous Decomposition Products

Toxic gases/vapours/fumes of carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Spill Cleanup Methods

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate, exhaust aerosol in well-ventilated area.

---

## 7. HANDLING AND STORAGE

---

**Usage Precautions** Keep away from heat, sparks and open flame

**Storage Precautions** Flammable/combustible. Keep away from oxidizers, heat and flames. May attack some plastics, rubber and coatings.

**Storage Criteria** Flammable compressed gas storage.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

Ingredient Name:	CAS No.	STD	LT EXP (8 hrs)	ST EXP (15 min)
Butane	106-97-8	OES	600 ppm	750 ppm

**Ingredient comments** Aerosol propellant

**Protective Gloves** Use protective gloves made of rubber (natural, latex)

**Ventilation** Well ventilated area

**Respirators** No specific recommendation made, but respiratory protection must be used  
If the general level Occupational Exposure Level (OEL)

**Eye Protection** Under normal use should not be required. Always direct nozzle away from the face

**Other Protection** Use in well ventilated area

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Colour</b>	colourless	<b>Appearance</b>	gas
---------------	------------	-------------------	-----

**Odour/taste** mild (or faint), disagreeable

**Physical Data Comments** this product is an aerosol using hydrocarbon propellants. The flammability data is based on these hydrocarbons.

**Solubility Description** Slightly soluble in water

<b>Specific Gravity (Water = 1)</b>	0.599 @ 20°C	<b>Mol Weight (At WT)</b>	58.14
-------------------------------------	--------------	---------------------------	-------

# SAFETY DATA SHEET

## RONSON BUTANE REFILL

Vapour Pressure (mmHg)	1520 @ 18°C	Vapour Density (air = 1)	2.05
Melting Point	-137 °C		
Flash Point	-60 °C	Flash Point Method	CC (closed cup)
Auto ignition Temperature	405 °C		
Flammability Limit	lower % 1.90		
Flammability Limit	upper % 8.50		

---

### 10. STABILITY AND REACTIVITY

---

Stability	Avoid heat, sparks and flames
Materials to avoid	Strong oxidizing agents
Conditions to avoid	Evaporates easily in air. Reacts strongly with oxidizers.
Hazardous Decomposition Products	Toxic gases/vapours/fumes of carbon monoxide (CO) carbon dioxide (CO <sub>2</sub> )

---

### 11. TOXICOLOGICAL INFORMATION

---

Toxic Conc.-LC50	680 ppm/2h (inh - mus)
Target organs	Central nervous system, eyes, respiratory system and lungs
Health Warnings	Gas or vapour displaces oxygen available for breathing (asphyxiant). Narcotic effect
Medical Symptoms	May cause suffocation. Dizziness.
Acute and chronic health hazards	Contact with liquid form may cause frostbite.

---

### 12. ECOLOGICAL INFORMATION

---

### 13. DISPOSAL CONSIDERATIONS

---

Disposal Methods	Vent to atmosphere
Empty Containers	Dispose of empty containers without puncturing <b>DO NOT INCINERATE</b>

---

### 14. TRANSPORT INFORMATION

---

<b>ROAD:</b>			
UN No	1950	Hazchem Code	2WE
ADR Class	2	ADR Item No.	3b
ADR Hazard No.	23 Flammable Gas		
CEPIC TEC ® No.	276	ADR Label No.	3
Label for conveyance			

# SAFETY DATA SHEET

## RONSON BUTANE REFILL

### AIR:

UN No. 1950 Air Transport Class No. 2  
AIR Sub Class 3

### SEA:

UN No. 1950 Sea Transport Class No. 2(2.1)

### RAIL:

Rail Transport Class No 2 Road PT. 3b

---

## 15. REGULATORY INFORMATION

---

Label for Supply

**Risk Phrases** R 10 Flammable

**Safety Phrases** S - 9 Keep container in well ventilated place  
S - 16 Keep away from sources of ignition - **NO SMOKING**  
S - 33 Take precautionary measures against Static discharges

---

## 16. OTHER INFORMATION

---

**-User Notes** This product is supplied in an aerosol form using a highly flammable gas as a propellant. Properly used for the intended purpose and in accordance to this safety data sheet should not present any undue hazard.

**Information Sources** Dangerous Properties of Industrial Chemicals, 6.edition, N.Sax, 1984  
OSHA Air Contaminants - Permissible Exposure Limits (Title 29)  
Handbook of Toxic and Hazardous Chemicals and Carcinogens, Sittig,'85  
Hazardous Materials, Emergency Response Guidebook, DOT-P 5800.3, 1984  
NIOSH/OSHA Pocket Guide to Chemical Hazards (latest edition)  
Threshold Limit Values and Biological Exposure Indices for 1994 - 95  
Chemical Safety Data Guide. Bureau of National Affairs , 1985

---

**SDS No:** 1001  
**Revision Date:** May 2000  
**Revision No./Replaces:** SDS issued 01 09 95  
**Revision Comments:** New Safety Data to CHIP format