

# MATERIAL SAFETY DATA SHEET

CARBON OFF

FILE NO.: 118636000

MSDS DATE: 8/23/11

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Carbon Off  
**MANUFACTURER:** DISCOVERY PRODUCTS  
**ADDRESS:** PO Box 399 Valley Park, MO 63088  
**PRODUCT USE:** Carbon Remover

**PRODUCT CODES:** 118636000  
**EMERGENCY PHONE:** 1-800-255-3924  
**CHEMTEL PHONE:** 1-800-255-3924  
**OTHER CALLS:** 636-464-6066

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT:</u>	<u>CAS NO.</u>	<u>PEL</u>	<u>TLV</u>	<u>%</u>
2-BUTOXY ETHANOL	111-76-2	50 ppm	20 ppm	1 - 5
ETHYL ALCOHOL	64-17-5	1000 ppm	1000 ppm	1 - 5
METHYL ALCOHOL	67-56-1	200 ppm	200 ppm	1 - 5
METHYLENE CHLORIDE	75-09-2	25 ppm	50 ppm	60 - 70
TOLUENE	108-88-3	100 ppm	50 ppm	1 - 5
PETROLEUM SULF ACID SALT	68608-26-4		10 ppm	1 - 5
PROPANE/N-BUTANE	68476-86-8	N/A	1000ppm	10 - 20

**SECTION 2 NOTES:** All of the ingredients contained in this product are listed on the TSCA inventory.

## SECTION 3: HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW:** Aerosol under pressure do not expose to high temperatures or store in direct sunlight. Pressure can cause can to burst.

**ROUTES OF ENTRY: EYES:** Irritation, reddening, inflammation and temporal eye damage. **SKIN:** May cause localized dryness, and defat the skin if over exposed. **INGESTION:** Gastric discomfort May cause nausea and/ or diarrhea, and absorption through gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness. **INHALATION:** May irritate respiratory tract, lungs, and may cause fatigue, nausea, vomiting and headache. Excessive exposure can cause dizziness and unconsciousness.

**ACUTE HEALTH HAZARDS:** See Above **CHRONIC HEALTH HAZARDS:** Dermatitis, Liver and Kidney damage.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Pre existing disorders with the skin, respiratory tract, liver, kidney, Central nervous system, heart, and auditory system will be aggravated by over exposure.

**CARCINOGENICITY:** **OSHA:** Yes **ACGIH:** Yes **NTP:** Yes **IARC:** Yes **OTHER:**

## SECTION 4: FIRST AID MEASURES

**EYES:** Flush with water for 15 minutes, lifting lower and upper eyelids occasionally. Contact physician if irritation persist.

**SKIN:** Wash with soap and water for 15 minutes. If irritation develops seek medical attention. **INGESTION:** Contact physician; do not induce vomiting unless directed by medical authority. Give large quantities of water if person is conscious. Get immediate medical attention. **INHALATION:** Move to fresh air. If not breathing administer artificial respiration. If breathing is difficult, give oxygen. Get medical attention. **NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

## SECTION 5: FIRE-FIGHTING MEASURES

**FLAMMABLE LIMITS IN AIR (% BY VOLUME):** LOWER: 1.2 UPPER: 10.6

**FLASH POINT:** F: N/A C: N/A **METHOD USED:**

**AUTOIGNITION TEMPERATURE:** F: N/A C: N/A

**NFPA HAZARD CLASSIFICATION:** HEALTH: 3 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **OTHER:**

**HMIS HAZARD CLASSIFICATION:** HEALTH: 3 **FLAMMABILITY:** 1 **REACTIVITY:** 0 **PROTECTION:** B

**EXTINGUISHING MEDIA:** ABC Dry chemical fire extinguisher, CO2, Water Spray or Alcohol-resistant foam.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear SCBA in fire situations. Do not use solid water spray for extinguishing media.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable. Contents under pressure. Exposure to high temperatures above 120F can cause bursting. Keep away from heat, sparks, and open flames. Flash point is based on liquid less propellant.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Phosgene, Hydrogen Chloride Gases & Nitrogen and Carbon oxides.

# MATERIAL SAFETY DATA SHEET

CARBON OFF

FILE NO.: 118636000

MSDS DATE: 8/23/11

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**ACCIDENTAL RELEASE MEASURES:** Remove any source of heat, flame, or sparks. Evacuate affected area. Mop up with appropriate absorbent material. Avoid breathing fumes ventilate area. Dispose of residue in accordance with federal, state and local guidelines. Do not reuse empty container. Do not puncture or incinerate container. Wrap container and place in trash collection. Small releases may be wiped up with wiping material.

---

## SECTION 7: HANDLING AND STORAGE

---

**HANDLING AND STORAGE:** Do not use or store near heat or open flame. Exposure to temperatures above 120 F may cause bursting. Use with adequate ventilation. Store in accordance with NFPA, state and local regulations.

**OTHER PRECAUTIONS:** None

**SECTION 7 NOTES:**

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### ENGINEERING CONTROLS:

**VENTILATION :** Normal, forced ventilation should not be required

**EYE PROTECTION:** Safety glasses are always recommended.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** N/A

**WORK HYGIENIC PRACTICES:** Wash hands after use.

**RESPIRATORY PROTECTION:** N/A

**SKIN PROTECTION:** N/A

**EXPOSURE GUIDELINES:**

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Hazy slight yellow liquid or spray.

**PHYSICAL STATE:** Liquid

**BOILING POINT:** F: >104 C: >40

**FREEZING POINT:** F: N/A C:

**EVAPORATION RATE (Butyl Acetate =1):** >2

**VAPOR PRESSURE (mmHg):** > 100 @ F: 68 C: 20

**VAPOR DENSITY (AIR = 1):** > 2 @ F: 68 C: 20

**SPECIFIC GRAVITY (H<sub>2</sub>O = 1):** 1.17 @ F: 68 C: 20

**PERCENT VOLATILE:** 91% BY WT/ BY VOL @ F: 77 C: 25

**VOLATILE ORGANIC COMPOUNDS (VOC):** WITH WATER: LBS/GAL WITHOUT WATER: LBS/GAL

**VISCOSITY:** 1404 @ F: 75 C: 23.89

**SECTION 9 NOTES:**

**ODOR:** Chlorinated Solvent

**pH AS SUPPLIED:** N/A

**MELTING POINT:** F: N/A C:

**PERCENT SOLIDS BY WEIGHT:** N/A

**SOLUBILITY IN WATER:** 95%

---

## SECTION 10: STABILITY AND REACTIVITY

---

**STABILITY:** STABLE X UNSTABLE

**CONDITIONS TO AVOID (STABILITY):** Moisture, heat, sparks, and open flames

**INCOMPATIBILITY (MATERIAL TO AVOID):** May attack certain plastics, rubber, & coatings. Incompatible w/ strong oxidizers & caustics, chemically active metal, such as Aluminum, magnesium powder, sodium, potassium, and lithium.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Phosgene, Hydrogen Chloride Gases, Nitrogen & Carbon oxides.

**HAZARDOUS POLYMERIZATION:** None

**CONDITIONS TO AVOID (POLYMERIZATION):** None

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

**TOXICOLOGICAL INFORMATION:** METHYLENE CHLORIDE - 75-09-2 – Oral rat LD50 1600 mg/kg, Inhalation rat LC50 52 g/m<sup>3</sup>

TOLUENE - 108-88-3 – Oral rat LD50: 636 mg/kg; skin rabbit LD50: 14100 uL/kg; inhalation rat LC50: 49 gm/m<sup>3</sup>/4H

# MATERIAL SAFETY DATA SHEET

CARBON OFF

FILE NO.: 118636000

MSDS DATE: 8/23/11

---

## SECTION 12: ECOLOGICAL INFORMATION

---

**ECOLOGICAL INFORMATION:** Do not let residue come in contact with waterways in the United States. Methylene Chloride - This material may leach into groundwater. Will quickly evaporate in the soil and water and may biodegrade to a moderate extent in the water. Will not significantly bioaccumulate. Released in the air this material is expected to have a half-life greater than 30 days.

**ENVIRONMENTAL TOXICITY:** LC50/96hr for fish - >100mg/l. Not expected to be toxic to aquatic life.

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, State and Federal regulations

---

## SECTION 14: TRANSPORT INFORMATION

---

**U.S. DEPARTMENT OF TRANSPORTATION:**

**HAZARD CLASS:**

**PACKING GROUP:**

**WATER TRANSPORTATION:**

**HAZARD CLASS:**

**PACKING GROUP:**

**AIR TRANSPORTATION:** Call manufacturer

**HAZARD CLASS:**

**PACKING GROUP:**

**PROPER SHIPPING NAME:** ORM-D

**ID NUMBER:**

**LABEL STATEMENT:**

**PROPER SHIPPING NAME:** Call manufacturer

**ID NUMBER:**

**LABEL STATEMENTS:**

**PROPER SHIPPING NAME:**

**ID NUMBER:**

**LABEL STATEMENTS:**

---

## SECTION 15: REGULATORY INFORMATION

---

### U.S. FEDERAL REGULATIONS

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** All Chemicals are listed

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):**

METHYLENE CHLORIDE - 75-09-2 - 1000

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):** None

**311/312 HAZARD CATEGORIES:** METHYLENE CHLORIDE - 75-09-2 – Acute: Yes Chronic: Yes Fire: No

Reactivity: No Pressure: No

**313 REPORTABLE INGREDIENTS:** 2-BUTOXY ETHANOL - 111-76-2, METHYL ALCOHOL - 67-56-1,

METHYLENE CHLORIDE - 75-09-2, TOLUENE - 108-88-3

**STATE REGULATIONS:** This product contains chemical(s) METHYLENE CHLORIDE - 75-09-2;

TOLUENE - 108-88-3 known to the state of California Proposition 65 to cause birth defects or other reproductive harm and cancer.

**INTERNATIONAL REGULATIONS:** Autralian Hazchem Code: 2Z and Inventory Status - yes; Canada Inventory Status -

DSL: yes NDSL: No; Korea Inventory Status – Yes;

### SECTION 15 NOTES:

---

## SECTION 16: OTHER INFORMATION

---

### OTHER INFORMATION:

**PREPARATION INFORMATION:** Juanita Mercure

**DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However there is no assumption of any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this MSDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.