# Exporters & Manufacturer

JRAL PROCESSED

## MATERIAL SAFETY DATA SHEET

To comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

SECTION I. IDENTITY OF PRODUCT AND IMPORTER OR PRODUCER

CORNWALL STONE

Trade Name: WG CORNISH STONE

As Marked on Bag: WG Cornish

Chemical Name: NaK<sub>2</sub>O.Al<sub>2</sub>O<sub>3</sub>.8SiO<sub>2</sub>(Variable)

Stone

CAS Number: Natural mixture of China Clay 1332-58-7, Feldspar 68476-25-5,

and Quartz 14808-60-7

Importer/Producer Name and Address:

. Telephone Number:

HAMMILL & GILLESPIE, INC.

For Emergency and Information

201/994/3650

Date Prepared: 11/22/85 Prepared By: R. P. Isaacs

SECTION II. HAZARDOUS INGREDIENTS

Total free silica (Quartz) by dry weight: 30% Much of this is not fine enough to be normally respirable.

See Section VI.

SECTION III. PHYSICAL DATA

Fusion Range: 1160-1175°C

Solubility in Water: Slight

Specific Gravity:

Vapor Pressure: Not Applicable

Odor and Appearance: White powder, odorless

% Volatile: 'Below 100 C. None

FIRE AND EXPLOSION HAZARD DATA: Non-flammable and Non-Hazardous SECTION IV. SECTION V. REACTIVITY DATA

Stability: Stable .

Incompatibility (Materials to Avoid): None Hazardous Polymerization: Will NOT occur

Data, information, and recommendations recorded herein are believed to be accurate. Hammill & Gillespie, Inc. makes no warranty, either expressed or implied, with respect thereto and disclaims all liability from reliance thereon.

(Continued on reverse side)

# SECTION VI. HEALTH HAZARD DATA

OSHA Permissable Exposure Limit (PEL): Total Dust mg/m³: 0.90

Respirable Dust\* mg/m³: 0.58

\*Based upon free silica content

Route of Entry: Inhalation

Effects of Overexposure:

Short Term - Probably no effect other than as a nuisance dust Long Term - Long term exposure to dust and free silica in concentrations higher than recommended PEL may cause silicosis.

First Aid: Eyes - Flush thoroughly with water. See a physician if irritation persists.

# SECTION VII. SPILL, LEAK AND DISPOSAL INFORMATION

Action to be taken in case material is released or spilled: Clean up and collect, minimizing excessive dust\*

Waste disposal method:

Amy approved solid waste disposal including burial.\*

\*Do not exceed recommended PEL - See Section VI.

### SECTION VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection: If dust concentrations exceed recommended Permissable Exposure Limits, use NIOSH approved dust respirators. If spraying coatings use NIOSH approved dust/mist respirators.

Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than Permissable Exposure Limits is recommended. Use adequate ventilation if spraying coatings.

Eye Protection: Wear tight fitting goggles if high dust concentrations exist.

Other Protective Equipment: Not required.

### SECTION IX. SPECIAL PRECAUTIONS

Minimize dust generation and exposure. Do not breathe dust.