



## MSDS - Material Safety Data Sheet

### I. Basic Information:

**Manufacturer:** RADIATOR SPECIALTY COMPANY

**Contact:** Robert Geer

**Address:** 600 RADIATOR ROAD

**Information Telephone Number:** 704-684-1811

**City, ST Zip:** INDIAN TRAIL, NC 28079

**Emergency Contact:** Rocky Mountain Poison Control Center

**Emergency Telephone Number:** 303-623-5716

**Country:**

**Emergency Restrictions:**

**Product Name:** LIQUID WRENCH INDUSTRIAL HEAVY DUTY SILICONE SPRAY

**MSDS No.:** PL911

**Issue Date:** 05/10/2010

**Supersedes Date:** 03/25/2009

### II. Hazards Identification:

#### EMERGENCY OVERVIEW

Flammable. Harmful or fatal if swallowed. Eye and Skin Irritant. Contents under Pressure.

Level 3 Aerosol

#### OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### Potential Health Effects

##### **Route(s) of Entry:**

Absorption, Eye, Inhalation, and Ingestion.

##### **Health Hazards (Acute and Chronic):**

See Signs and Symptoms below

##### **Signs and Symptoms:**

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis.

Ingestion: HARMFUL OR FATAL IF SWALLOWED.

##### **Medical Conditions Generally Aggravated by Exposure:**

Unknown

##### **Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema, which is a potentially fatal condition.

#### Potential Environmental Effects

Not Available

### III. Composition/Information on Ingredients:

## MSDS - Material Safety Data Sheet

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
Aliphatic Hydrocarbon Solvent	8052-41-3	40.0 - 70.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Dimethyl Polysiloxane	63148-62-9	3.0 - 7.0	
Hydrocarbon Fluid	64742-47-8	15.0 - 40.0	
Mesitylene	108-67-8	1.0 - 5.0	
Naphthenic Petroleum Distillate	64742-52-5	1.0 - 5.0	
Xylene (mixed isomers)	1330-20-7	1.0 - 5.0	
Ethylbenzene	100-41-4	0.1 - 1.0	

### IV. First Aid Measures:

#### Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 20 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash skin with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Remove and isolate contaminated clothing. Launder contaminated clothing before reuse.

Inhalation: Move victim to fresh air. If breathing becomes difficult, administer oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

#### Note to Physicians:

N/E

### V. Fire Fighting Measures:

#### Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, and Dry Chemical

#### Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

#### Products of Combustion:

Normal products of combustion, carbon dioxide, smoke and Nitrogen and Sulfur Oxides

#### Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

### VI. Accidental Release Measures:

#### Personal Precautions:

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean up has been completed.

#### Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

#### Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

#### Methods for Cleanup:

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

#### Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

### VII. Handling and Storage:

#### Handling Precautions:

Handling Use with adequate ventilation and proper protective equipment. Do not use near fire, sparks, or flame. Do not puncture or incinerate container. Avoid contact with eyes. Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent over-exposure. Avoid contact with eyes. Keep Away From Children and Animals.

# MSDS - Material Safety Data Sheet

## Storage Precautions:

Store in cool, well-ventilated area below 120°F away from heat, fire, sparks or flame. Keep away from oxidizers and acids.

## **VIII. Exposure Controls/Personal Protection:**

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Aliphatic Hydrocarbon Solvent	100 ppm	100 ppm	Not Available
Mesitylene	N/A	N/A	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Xylene (mixed isomers)	100 ppm (TWA)	100 ppm (TWA)	Not Available
Dimethyl Polysiloxane	N/E	N/E	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Not Available
Hydrocarbon Fluid	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Not Available

## Engineering Controls:

See Section above for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

## Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

## **IX. Physical and Chemical Properties:**

**Boiling Point:** 310°F

**Boiling Range:** N/D

**Solubility in Water:** Insoluble

**Flash Point:** 105°F

**Odor Threshold:** N/D

**Vapor Density (AIR = 1):** N/D

**pH Range:** N/A

**Decomposition Temp:** N/D

**Lower Explosive Limit:** N/D

**Specific Gravity (H<sub>2</sub>O = 1):** 0.82

**Other Information:** N/E

**Melting Point:** N/A

**Freezing Point:** N/D

**Flash Point Method:** TCC

**Evaporation Rate (Butyl Acetate = 1):** N/D

**Appearance and Odor:** Clear to slight yellow liquid with petroleum odor.

**Vapor Pressure (mm Hg.):** N/D

**Partition Coefficient:** N/D

**Auto-Ignition Temp:** N/D

**Upper Explosive Limit:** N/D

## **X. Stability and Reactivity:**

### Stability:

Stable

### Conditions to Avoid:

Avoid heat, sparks, and flames. Avoid incompatible materials.

### Incompatible Materials:

Oxidizing agents and acids.

### Hazardous Decomposition Products:

Normal products of combustion, carbon dioxide, smoke and Nitrogen and Sulfur Oxides

### Possibility of Hazardous Reactions:

Will not occur

## **XI. Toxicological Information:**

N/D

# MSDS - Material Safety Data Sheet

## XII. Ecological Information:

N/D

## XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

## XIV. Transport Information:

Shipping Name: Consumer Commodity  
DOT Hazard Class: ORM-D

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)  
UN number: UN1950  
Shipping Name: Aerosols  
Class: 2.1

International:

ICAO/IATA  
UN number: UN1950  
Shipping Name: Aerosols  
Class: 2.1

IMDG  
UN number: UN1950  
Shipping Name: Aerosols  
Class: 2.  
EMS: F-D, S-U

## XV. Regulatory Information:

SARA 313 Reportable Chemicals:  
1,2,4-Trimethylbenzene - 95-63-6  
Xylene - 1330-20-7  
Ethylbenzene - 100-41-4

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

State RTK Chemicals:  
Aliphatic Hydrocarbon - 8052-41-3  
1,2,4-Trimethylbenzene - 95-63-6  
1,3,5-Trimethylbenzene - 108-67-8  
Xylene -1330-20-7

# MSDS - Material Safety Data Sheet

## XVI. Other Information:


- Chemical State:**  Liquid  Gas  Solid
- Chemical Type:**  Pure  Mixture
- Hazard Category:**
- Acute  Chronic  Fire  Pressure  Reactive



### Additional Manufacturer Warnings:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established  
 N/D: Not Determined  
 N/A: Not Applicable  
 N/AV: Not Available



### Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this MSDS. The user is responsible for full compliance.