# **Datey**®

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Oatey PVC Heavy Duty Clear or Gray Cement

Other means of identification

SDS number 1102EV

**Synonyms** Part Numbers: 30850,30850V, 30863 30863V, 30876, 30876V, 30882, 31008, 31008V,

31011, 31011R, 31011V, 31950, 31951, 31952, 31953, 31953R, 30349, 31093, 31093V, 31094, 31094V, 31095, 31095V, 31105, 31105V, 31118, 31118V, 31978, 31979, 31980, 31981, 32050,

32051, 32052, 32210, 32211

Recommended use Joining PVC Pipes
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Oatey Co.

Address 4700 West 160th St.

Cleveland, OH 44135

Telephone 216-267-7100 E-mail info@oatey.com

**Transport Emergency** Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015
Contact person MSDS Coordinator

## 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters

airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May

cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a

well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If

eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse. In case of fire: Use appropriate media to extinguish.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Oatey PVC Heavy Duty Clear or Gray Cement
920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014

## Hazard(s) not otherwise classified (HNOC)

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

#### Supplemental information

Not applicable.

# 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name             | CAS number  | %     |  |
|---------------------------|-------------|-------|--|
| Furan, Tetrahydro-        | 109-99-9    | 30-60 |  |
| 2-Propanone               | 67-64-1     | 10-30 |  |
| Cyclohexanone             | 108-94-1    | 10-30 |  |
| Polyvinyl chloride        | 9002-86-2   | 10-30 |  |
| Methyl ethyl ketone       | 78-93-3     | 5-10  |  |
| Colloidal silicon dioxide | 112945-52-5 | 1-5   |  |

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Skin contact

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin

irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, Ingestion keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

**General information** 

cause redness and pain. Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation.

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May

oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed. Take off all contaminated clothing immediately. IF exposed or concerned: Get medical

advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# **Environmental precautions**

7. Handling and storage Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

Value

**Form** 

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

U.S. - OSHA
Components

| · · ·   · · · · · · · · ·                      | -71                         | T UI U     |              |
|--|-----------------------------|------------|--------------|
| Colloidal silicon dioxide<br>(CAS 112945-52-5) | TWA                         | 0.8 mg/m3  | Unspecified. |
|  |                             | 20 mppcf   | Unspecified. |
| US. OSHA Specifically Regulated S              | Substances (29 CFR 1910.100 |            | •            |
| Components                                     | Туре                        | Value      |              |
| Polyvinyl chloride (CAS<br>9002-86-2)          | STEL                        | 5 ppm      |              |
| ,  | TWA                         | 1 ppm      |              |
| US. OSHA Table Z-1 Limits for Air              | Contaminants (29 CFR 1910.1 | 1000)      |              |
| Components                                     | Туре                        | Value      | Form         |
| 2-Propanone (CAS 67-64-1)                      | PEL                         | 2400 mg/m3 |              |
|  |                             | 1000 ppm   |              |
| Cyclohexanone (CAS<br>108-94-1)                | PEL                         | 200 mg/m3  |              |
| ,  |                             | 50 ppm     |              |
| Furan, Tetrahydro- (CAS<br>109-99-9)           | PEL                         | 590 mg/m3  |              |
| •  |                             | 200 ppm    |              |
|  |                             |            |              |

Oatey PVC Heavy Duty Clear or Gray Cement

SDS US

920700 Version #: 03 Revision date:7-01-2022 Issue date:8-4-2014

Type

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components   | Туре          | Value  | Form                 |
|--|---------------|--|----------------------|
| Methyl ethyl ketone (CAS                             | PEL           | 590 mg/m3                                    |                      |
| 78-93-3)   |               | 200 ppm                                      |                      |
| Polyvinyl chloride (CAS                              | PEL           | 5 mg/m3                                      | Respirable fraction. |
| 9002-86-2)   |               | 15 mg/m3                                     | Total dust.          |
| JS. OSHA Table Z-3 (29 CFR 1910                      | .1000)        | 10 mg/mo                                     | rotal adot.          |
| Components   | Туре          | Value  |                      |
| Colloidal silicon dioxide<br>(CAS 112945-52-5)       | TWA           | 0.8 mg/m3                                    |                      |
| (0/10/1/2040/02/0)                                   |               | 20 mppcf                                     |                      |
| US. ACGIH Threshold Limit Values                     | 5             |  |                      |
| Components   | Туре          | Value  | Form                 |
| 2-Propanone (CAS 67-64-1)                            | STEL          | 750 ppm                                      |                      |
|  | TWA           | 500 ppm                                      |                      |
| Cyclohexanone (CAS<br>108-94-1)                      | STEL          | 50 ppm                                       |                      |
| ,  | TWA           | 20 ppm                                       |                      |
| Furan, Tetrahydro- (CAS<br>109-99-9)                 | STEL          | 100 ppm                                      |                      |
| ,  | TWA           | 50 ppm                                       |                      |
| Methyl ethyl ketone (CAS<br>78-93-3)                 | STEL          | 300 ppm                                      |                      |
|  | TWA           | 200 ppm                                      |                      |
| Polyvinyl chloride (CAS<br>9002-86-2)                | TWA           | 1 mg/m3                                      | Respirable fraction. |
| U.S NIOSH  |               |  |                      |
| Components   | Туре          | Value  | Form                 |
| Colloidal silicon dioxide                            | REL           | 6 mg/m3                                      | Unspecified.         |
| (CAS 112945-52-5)<br>US. NIOSH: Pocket Guide to Chem | nical Hazards |  |                      |
| Components   | Туре          | Value  |                      |
| 2-Propanone (CAS 67-64-1)                            | TWA           | 590 mg/m3                                    |                      |
| . ,  |               | 250 ppm                                      |                      |
| Colloidal silicon dioxide<br>(CAS 112945-52-5)       | TWA           | 6 mg/m3                                      |                      |
| CAS 112945-52-5)<br>Cyclohexanone (CAS<br>108-94-1)  | TWA           | 100 mg/m3                                    |                      |
| 100 0 <del>1</del> -1 <i>)</i>                       |               | 25 ppm                                       |                      |
| Furan, Tetrahydro- (CAS<br>109-99-9)                 | STEL          | 735 mg/m3                                    |                      |
| 109-99-9)  |               | 250 ppm                                      |                      |
| 109-99-9)  |               | -00 pp                                       |                      |
| 109-99-9)  | TWA           | 590 mg/m3                                    |                      |
| ,  |               | 590 mg/m3<br>200 ppm                         |                      |
| Methyl ethyl ketone (CAS<br>78-93-3)                 | TWA<br>STEL   | 590 mg/m3                                    |                      |
| Methyl ethyl ketone (CAS                             | STEL          | 590 mg/m3<br>200 ppm<br>885 mg/m3<br>300 ppm |                      |
| Methyl ethyl ketone (CAS                             |               | 590 mg/m3<br>200 ppm<br>885 mg/m3            |                      |

Oatey PVC Heavy Duty Clear or Gray Cement

920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014 4 / 10

### **Biological limit values**

# **ACGIH Biological Exposure Indices**

| Components                        | Value      | Determinant                                 | Specimen | Sampling Time |  |
|-----------------------------------|------------|---|----------|---------------|--|
| 2-Propanone (CAS 67-64-           | 1) 50 mg/l | Acetone                                     | Urine    | *             |  |
| Cyclohexanone (CAS 108-94-1)      | 80 mg/l    | 1,2-Cyclohexan<br>ediol, with<br>hydrolysis | Urine    | *             |  |
|                                   | 8 mg/l     | Cyclohexanol, with hydrolysis               | Urine    | *             |  |
| Furan, Tetrahydro- (CAS 109-99-9) | 2 mg/l     | Tetrahydrofura<br>n                         | Urine    | *             |  |
| Methyl ethyl ketone (CAS 78-93-3) | 2 mg/l     | MEK   | Urine    | *             |  |

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-1) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin. Furan, Tetrahydro- (CAS 109-99-9) Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards** 

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

## Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

**General hygiene** considerations

When using, do not eat, drink or smoke. Wash hands after handling and before eating.

## 9. Physical and chemical properties

**Appearance** Opaque.or Translucent.

Liquid. Physical state **Form** Liquid. Color Gray or Clear. Odor Solvent. Not available. **Odor threshold** 

Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

range

151 °F (66.11 °C)

14.0 - 23.0 °F (-10.0 - -5.0 °C) Flash point

**Evaporation rate** 

Oatey PVC Heavy Duty Clear or Gray Cement 920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014 5/10 Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 145 mm Hg @ 20 C

Vapor density 2.5

Relative density 0.88 - 0.92

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity1200 - 2500 cP

Other information

Bulk density 7.5 lb/gal

VOC (Weight %) See Can Label

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause

headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause

irritation to the respiratory system.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

Ingestion May be fatal if swallowed and enters airways. Harmful if swallowed.

Symptoms related to the physical, chemical and

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness,

toxicological characteristics nausea and vomiting.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Components Species Test Results

Cyclohexanone (CAS 108-94-1)

**Acute**Dermal

LD50 Rabbit 948 mg/kg

Inhalation

LC50 Rat 8000 ppm, 4 hours

Oatey PVC Heavy Duty Clear or Gray Cement SDS US
920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014 6 / 10

**Species Test Results** Components

Oral

Rat LD50 1540 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eve damage/eve

irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

Respiratory sensitization Not available.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Suspected of causing cancer. In 2012 USEPA Integrated Risk Information System (IRIS) Carcinogenicity

reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure. This product contains polyvinyl chloride (PVC) that is not a fabricated product, and is therefore, defined and regulated as a toxic and hazardous substance under 29 C.F.R. § 1910.1017 due to the presumed presence of residual vinyl chloride monomer. The concentrations

of residual vinyl chloride calculated to be contained in this product are well below the threshold for

classification in accordance with 29 C.F.R. § 1910.1200.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Colloidal silicon dioxide (CAS 112945-52-5) 3 Not classifiable as to carcinogenicity to humans. Cyclohexanone (CAS 108-94-1) 3 Not classifiable as to carcinogenicity to humans. Polyvinyl chloride (CAS 9002-86-2) 3 Not classifiable as to carcinogenicity to humans.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Polyvinyl chloride (CAS 9002-86-2) Cancer

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Respiratory tract irritation. Narcotic effects.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results** 

Cyclohexanone (CAS 108-94-1)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

No data available. Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow) 2-Propanone (CAS 67-64-1)

Cyclohexanone (CAS 108-94-1) 0.81 Furan, Tetrahydro- (CAS 109-99-9) 0.46 Methyl ethyl ketone (CAS 78-93-3) 0.29

Mobility in soil No data available.

Oatey PVC Heavy Duty Clear or Gray Cement 920700 Version #: 03 Revision date: 7-01-2022 7/10 Issue date: 8-4-2014

-0.24

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material **Disposal instructions** 

> and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

## 14. Transport information

DOT

UN1133 UN number Adhesives **UN proper shipping name** 

Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

T11, TP1, TP8, TP27 **Special provisions** 

150 **Packaging exceptions** Packaging non bulk 201 Packaging bulk 243

**IATA** 

UN1133 **UN number** UN proper shipping name Adhesives

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN number** UN1133 **UN** proper shipping name **ADHESIVES** 

Transport hazard class(es)

3 Subsidiary risk Packing group Ш **Environmental hazards** 

Marine pollutant No. **EmS** F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Oatey PVC Heavy Duty Clear or Gray Cement 8/10 920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014

SDS US

## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Polyvinyl chloride (CAS 9002-86-2)

Central nervous system

Liver Rlood Flammability

#### CERCLA Hazardous Substance List (40 CFR 302.4)

2-Propanone (CAS 67-64-1) LISTED Cyclohexanone (CAS 108-94-1) LISTED Furan, Tetrahydro- (CAS 109-99-9) LISTED Methyl ethyl ketone (CAS 78-93-3) LISTED

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

## SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

No

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

## Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

2-Propanone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714

# Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-Propanone (CAS 67-64-1) 35 %WV Methyl ethyl ketone (CAS 78-93-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

2-Propanone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714

## **US** state regulations

#### US. Massachusetts RTK - Substance List

2-Propanone (CAS 67-64-1)

Colloidal silicon dioxide (CAS 112945-52-5)

Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

#### US. New Jersey Worker and Community Right-to-Know Act

2-Propanone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

Oatey PVC Heavy Duty Clear or Gray Cement 9/10

920700 Version #: 03 Revision date: 7-01-2022 Issue date: 8-4-2014

Polyvinyl chloride (CAS 9002-86-2)

## US. Pennsylvania Worker and Community Right-to-Know Law

2-Propanone (CAS 67-64-1)

Colloidal silicon dioxide (CAS 112945-52-5)

Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

#### US. Rhode Island RTK

2-Propanone (CAS 67-64-1) Cyclohexanone (CAS 108-94-1) Furan, Tetrahydro- (CAS 109-99-9) Methyl ethyl ketone (CAS 78-93-3)

#### **US. California Proposition 65**

▲ WARNING: This product can expose you to chemicals including Tetrahydrofuran, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

See Section 11 for additional information.

#### **International Inventories**

Country(s) or region

| Australia   | Australian Inventory of Chemical Substances (AICS)                     | Yes |
|-------------|--|-----|
| Canada      | Domestic Substances List (DSL)   | Yes |
| Canada      | Non-Domestic Substances List (NDSL)                                    | No  |
| China       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes |
| Europe      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No  |
| Europe      | European List of Notified Chemical Substances (ELINCS)                 | No  |
| Japan       | Inventory of Existing and New Chemical Substances (ENCS)               | Yes |
| Korea       | Existing Chemicals List (ECL)  | Yes |
| New Zealand | New Zealand Inventory  | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes |

On inventory (yes/no)\*

Yes

Toxic Substances Control Act (TSCA) Inventory

## 16. Other information, including date of preparation or last revision

Inventory name

Issue date 04-August-2014 07-01-2022 **Revision date** 

Version # 03 Health: 2 **HMIS®** ratings

United States & Puerto Rico

Flammability: 3 Physical hazard: 0

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available.

SDS US 920700 Version #: 03 Revision date: 7-01-2022 10 / 10 Issue date: 8-4-2014

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).