

MATERIAL SAFETY DATA SHEET

4-4968 OFFSET GLAZE REMOVER

Revision Date: 5/15/12

Section I - Product Identification

Manufacturer's Name Presstek	Emergency Phone Number (24 Hours) CHEMTREC @ (800)424-9300
Street Address 55 Executive Drive	MSDS Request Phone Number: 1-603-595-7000
City, State, Zip Code Hudson, NH 03051	For MSDS via Fax: 1-800-995-0088
Product Use: OFFSET PRINTING.	Date Prepared: February 2, 1995
	Prepared By: Kenneth W. Pinter

Chemical Name, Trade Name, Synonyms: NONE.

HMIS RATING

2 - Health 2 - Flammability 0 - Reactivity B - Personal Protection

Section II - Hazardous Ingredients

Hazardous Components	CAS NO.	% WT.	Exposure Limits		
			OSHA PEL	ACGIH TLV	OTHER
PETROLEUM DISTILLATE (ISOPARAFFINIC)	64742-48-9	65-75	NOT ESTABLISHED.	NOT ESTABLISHED.	300PPM
HEXYLENE GLYCOL	107-41-5	15-20	25 PPM(C).	25 PPM(C).	
2-BUTOXY ETHANOL (BUTYL CELLOSOLVE)	111-76-2	10-12	25 PPM.	25 PPM	
PETROLEUM DISTILLATE (AROMATIC)	64742-94-5	< 6	NOT ESTABLISHED. (C): CEILING.	NOT ESTABLISHED	

Section III - Physical Data

Boiling POINT(F): 325-375	pH: N.A.
Vapor Pressure(mm Hg): < 10	Freezing Point(F): N.A.
Vapor Density (AIR = 1): CA. 5	VOC: 6.6 LBS/GAL
Specific Gravity (H2O=1): 0.792	Color And Odor: CLEAR / Kerosine
Odor Threshold: N.D.	Physical State: LIQUID
Evaporation Rate (Butyl Acetate = 1): N.D.	
Solubility in Water: INSOLUBLE.	

Section IV - Fire and Explosion Hazard Data

FLASH POINT (METHOD USED): 105(F) T.C.C.	Flammable Limits: LEL: 0.8% UEL: 7%
Auto-ignition Temperature: N.D.	
Extinguishing Media: FOAM / CO2 / DRY CHEMICAL.	
Special Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.	
Unusual Fire And Explosion Hazards: KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.	

Section V - Reactivity Data

Stability Unstable :	Conditions to Avoid: SOURCES OF IGNITION. MATERIAL IS COMBUSTIBLE.
Stable : X	

MATERIAL SAFETY DATA SHEET

4-4968 OFFSET GLAZE REMOVER

Revision Date: 5/15/12

Incompatibility (Materials to Avoid): OXIDIZING MATERIAL.

Hazardous Decomposition Products: CO / CO2 / SMOKE.-----
Hazardous | May Occur: | Conditions to Avoid: NONE.
Polymerization | Will Not Occur: X |**Section VI - Health Hazard Data (Acute and Chronic)**

Primary Route(s) of Entry: SKIN, INHALATION.

Oral Ingestion: MODERATELY TOXIC.-----
Eye Contact: MAY CAUSE MODERATE TO SEVERE IRRITATION.-----
Skin Contact: PROLONGED CONTACT MAY LEAD TO IRRITATION AND DERMATITIS.-----
Inhalation: PROLONGED INHALATION MAY RESULT DAMAGE TO KIDNEYS, LUNGS AND RED BLOOD CELLS.-----
Effects of Overexposure: MAY CAUSE HEADACHE, NAUSEA, VOMITING, DROWSINESS AND UNCONSCIOUSNESS.-----
Medical Conditions Generally | MAY AGGRAVATE AN EXISTING DERMATITIS.
Aggravated by Exposure |-----
Carcinogenicity: CONTAINS NO KNOWN CARCINOGENS IN EXCESS OF .1%.-----
Mutagenicity: NOT KNOWN TO BE MUTAGENIC.-----
Teratogenicity: NOT KNOWN TO BE TERATOGENIC.-----
Reproductive Toxicity: NOT KNOWN TO HAVE REPRODUCTIVE TOXICITY.-----
FIRST AID PROCEDURES-----
Ingestion: DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.-----
Eye: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS CALL A PHYSICIAN.-----
Skin: REMOVE ANY CONTAMINATED CLOTHING AND WASH SKIN WITH SOAP AND WATER.-----
Inhalation: REMOVE TO FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT.
GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING.**Section VII - Toxicology Information**

Ingredient	Inhalation	Oral	Dermal
	LC50	LD50 (RATS)	LD50 (RABBITS)
PETROLEUM DIST. (ISOP.)	N.D.	N.D.	N.D.
HEXYLENE GLYCOL	NO DEATHS (RATS) IN SATURATED AIR.	4 g/KG	13.3 mg/KG
2-BUTOXY ETHANOL	700PPM (7HRS)	0.5-3.0 g/KG	0.4 g/KG
PETROLEUM DIST. (AROMATIC)	N.D.	N.D.	N.D.

Section VIII - Spill or Leak Procedure-----
Steps to be taken in case material is released or spilled:
REMOVE ALL SOURCES OF IGNITION. WIPE UP AND DISPOSE OF AS FOR COMBUSTIBLE OR (FLAMMABLE) MATERIALS.

MATERIAL SAFETY DATA SHEET

4-4968 OFFSET GLAZE REMOVER

Revision Date: 5/15/12

Disposal Method: IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS FOR COMBUSTIBLE (OR FLAMMABLE) MATERIALS.

Section IX - Special Protection Information

Ventilation Local Exhaust: N.A. Special: N.A.
Mechanical(General): ACCEPTABLE. Other: N.A.

Respiratory Protection: NOT NORMALLY NECESSARY.

Protective Clothing: WEAR IMPERVIOUS GLOVES TO AVOID PROLONGED OR REPEATED CONTACT.

Eye Protection: SPLASH GOGGLES.

Other Protective Equipment: NOT NORMALLY NECESSARY.

Section X - Special Precautions

Precautions to be taken in Handling and Storing: SAME AS FOR ANY COMBUSTIBLE MATERIAL WITH A TCC FLASH 105(F). KEEP CONTAINER CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME. AVOID INHALATION.

Other Precautions: NONE.

Section XI - Transportation Information

DOT Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. (NAPTHA),3, UN1268
NOTE: PACKAGE SIZE QUALIFIES FOR ORMD

Section XII - Regulatory Information

CERCLA/SUPERFUND,40 CFR 117,302: THIS PRODUCT DOES NOT CONTAIN ANY REPORTABLE QUANTITY (RQ) SUBSTANCE.

SARA(TITLE III) - Sections 302, 311, 312, and 313:

Section 302 Extremely Hazardous Substances (40 CFR 355): THIS PRODUCT DOES NOT CONTAIN ANY INGREDIENTS LISTED AS AN EXTREMELY HAZARDOUS SUBSTANCE.

Section 311 and 312 MSDS Submission and Inventory Reporting (40 CFR 370): THIS PRODUCT CONTAINS MATERIALS THAT MAY RQUIRE REPORTING UNDER 311 AND 312 IF STORED IN LARGE ENOUGH QUANTITIES.

Section 313 Toxic Chemical Release Reporting (40 CFR 372): THIS PRODUCT DOES NOT CONTAIN ANY INGREDIENTS ON THE LIST OF TOXIC CHEMICALS.

TOXIC SUBSTANCES CONTROL ACT (TSCA):
This product complies with rules and regulations of TSCA.

California Proposition 65: THIS PRODUCT CONTAINS A CHEMICAL (BENZENE < 1PPM) AS A CONTAMINANT THAT IS LISTED BY THE STATE OF CALIFORNIA AS CARCINOGEN UNDER PROPOSITION 65.

Section XIII - Addition Information

NONE

N.D. = No Data N.A. = Not Applicable

The information herein given in good faith but no warranty, express or implied, is made.