

===== Product Identification =====

MSDS NAME:OLYMPIC SEMI-TRANSPARENT OIL STAIN-900 SERIES

NIIN:00D030065

MSDS Number: BTLCN

=== Responsible Party ===

Company:THE OLYMPIC HOMECARE PRODUCTS COMPANY

Address:2233 112TH AVENUE NE

City:BELLEVUE

State:WA

ZIP:98004

Country:US

Info Phone Num:206-453-1700

Emergency Phone Num:206-453-1700

CAGE:EO413

=== Contractor Identification ===

Company:THE OLYMPIC HOMECARE PRODUCTS COMPANY

Address:2233 112TH AVENUE NE

Box:City:BELLEVUE

State:WA

ZIP:98004

Country:US

Phone:206-453-1700

CAGE:EO413

===== Composition/Information on Ingredients =====

Name:NAPHTHA, HEAVY ALKYLATE (INGREDIENTS 1-3 EQUAL 40-80 % OF TOTAL)

CAS:64741-65-7

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE (INGREDEINTS 1-3 = 40-80% OF THE TOTAL)

CAS:64742-47-8

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Name:NAPHTHA, MEDIUM ALIPHATIC (INGREDIENTS 1-3 EQUAL 40-80% OF THE TOTAL)

CAS:64742-88-7

Other REC Limits:NONE RECOMMENDED

Name:MAGNESIUM SILICATE

CAS:1480-96-6

Fraction by Wt: 2-11% %

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:TLV (MINERAL SPIRITS) = 50 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HARMFUL OR FATAL IF SWALLOWED. SEVERE

SKIN IRRITANT UPON PROLONGED CONTACT. SLIGHT EYE IRRITANT. REPEATED OR PROLONGED EXPOSURE MAY RESULT IN CENTAL NERVOUS SYSTEM DEPRESSION. OVEREXPOSURE TO MAGNESIU M SILICATE, WHICH MAY OCCUR WHILE SANDING, MAY CAUSE PERMANENT LUNG IMPAIRMENT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:SKIN IRRITATION, EYE IRRITATION, DIZZINESS, HEADACHES, UNCONSCIOUSNESS, BRAIN DAMAGE, NERVOUS SYSTEM DAMAGE, LUNG IMPAIRMENT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:105F,41C

Lower Limits:1 %

Upper Limits:6 %

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACE-PIECE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:TO AVOID SPONTANEOUS CONMBUSTION OF OILY CLOTHES AND RAGS, SOAK IN WATER AFTER USE OR PLACE IN A CLOSED METAL CONTAINER AWAY FROM IGNITION SOURCES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION IN VICINITY OF SPILL. VENTILATE WITH NON-SPRAKING FAN TO RELEASE VAPORS. CLEAN UP SPILLS AS SOON AS POSSIBLE. ABSORB SPILL WITH CLAY OR DIATMOACEOUS EARTH.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP OUT OF REACH OF CHILDREN. USE ONLY IN WELL VENTILATED AREA. DO NOT USE OR STORE NEAR OPEN FLAME. AVOID EYE AND SKIN CONTACT.

Other Precautions:AVOID INHALATION OF VAPOR OR MIST. AVOID BREATHING DUST WHILE SANDING. DO NOT DRINK ALCOHOL WHILE WORKING WITH THIS PRODUCT. DO NOT DRIVE, OPERATE MACHINERY OR CLIMB LADDERS IF YOOU EXPERIENCE HEADACH ES, NAUSEA OR DIZZINESS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR

SELECTION.

Ventilation:USE GENERAL VENTILATION (FAN, OPEN WINDOWS, DOORS) TO KEEP MINERAL SPIRITS EXPOSURE LEVEL BELOW THE TLV.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GOGGLES OR GLASSES

Other Protective Equipment:USE DUST RESPIRATOR WHILE SANDING.

Work Hygienic Practices:MINIMIZE SKIN AND EYE CONTACT AND INHALATION OF VAPOR AND MIST. AVOID INHALATION OF DUST WHILE SANDING.

Supplemental Safety and Health

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315F,157C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:2

Vapor Density:4.9

Spec Gravity:N/K

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:INSOLUBLE

Appearance and Odor:THIN LIQUID, MILD ODOR, VARIOUS COLORED STAINS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:EXTREME TEMPERATURES, SPARKS, OPEN FLAMES

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

*** END OF RECORD ***