

=====
Product Identification
=====

MSDS NAME:241 68 MOORE'S INTERIOR WOOD PENETRATING STAIN

NIIN:00F020160

MSDS Number: BMHXC

=== Responsible Party ===

Company:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE RD

City:MONTVALE

State:NJ

ZIP:07645

Info Phone Num:(201) 344-1200

Emergency Phone Num:(201) 344-1200

CAGE:09585

=== Contractor Identification ===

Company:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE RD

City:MONTVALE

State:NJ

ZIP:07645

Country:US

Phone:201-573-9600

CAGE:09585

Company:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE RD

Box:City:MONTVALE

State:NJ

ZIP:07645

Country:US

Phone:201-573-9600

CAGE:91950

=====
Composition/Information on Ingredients
=====

Name:2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL
CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 6-14%

Other REC Limits:25 PPM (SKIN)

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES
MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 67-75%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION: NARCOSIS, HARMFUL & FATAL.

EYES: IRRITATION. INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM

DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INGESTION: NARCOSIS, HARMFUL & FATAL. EYES:
IRRITATION. INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====
First Aid Measures
=====

First Aid:INGESTION: GIVE 1 OR 2 GLASSES OF WATER. EYES: FLUSH W/PLENTY
OF WATER. SKIN: WASH W/MILD SOAP & WATER. OBTAIN MEDIAL ATTENTION
IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point:110F

Lower Limits:1%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG

Fire Fighting Procedures:DON'T USE WATER STREAM ON BURNING LIQUID. COOL
EXPOSED CONTAINERS W/WATER.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. USE
NON-SPARKING TOOLS TO RETURN MATERIALS TO CONTAINERS. ABSORB
RESIDUE W/FULLER'S EARTH.

=====
Handling and Storage
=====

Handling and Storage Precautions:CLOSE CONTAINER AFTER EACH USE. USE
ONLY W/ADEQUATE VENTILATION. AVOID CONTACT W/SKIN. AVOID BREATHING
VAPOR/SPRAY MIST. DON'T TAKE INTERNALLY.

Other Precautions:KEEP OUT OF REACH CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR SPECIFIED FOR
PROTECTION AGAINST PAINT SPRAY MIST & ORGANIC VAPORS IN RESTRICTED
OR CONFINED AREAS.

Ventilation:MECHANICAL EXHAUST: ADEQUATE TO KEEP AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:88%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HEAT & FLAME

Hazardous Decomposition Products:CO & CO2

=====
Disposal Considerations
=====

Waste Disposal Methods:DON'T INCINERATE SEALED CONTAINERS. DISPOSE OF
IN CONVENTIONAL PROCEDURES ACCORDING TO LOCAL, STATE, & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

*** END OF RECORD ***