MSDS: A9205

ITEM: 2C991 - Remover/Cleaner

ORDER: 0136866880

LP NUMBER: U245753860-A

MATERIAL SAFETY DATA SHEET (MSDS)

MATERIAL			

Associated Grainger Items 2C991, 9GZR3

MATERIAL SAFETY DATA SHEET

ITW DYKEM(R*)

HMIS(R*): HEALTH 1 FLAMMABILITY REACTIVITY PERSONAL PROTECTION B

- SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION -

IDENTITY: REMOVER & CLEANER

ITEM NO.: 82038 FORMULA: 8947A

ANOTHER EXCLUSIVE PRODUCT OF: ITW DYKEM

ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE): 805 EAST OLD 56 HIGHWAY OLATHE, KS 66061-4914

EMERGENCY TELEPHONE NUMBER: 1-800-535-5053 (DOMESTIC) 1-352-323-3500 (INTERNATIONAL)

TELEPHONE NUMBER FOR INFORMATION: 1-800-443-9536 OR 1-913-397-9889

PRODUCT CLASS: REMOVER & CLEANER (AEROSOL)

BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

DATE PREPARED: 9/4/06

SIGNATURE OF PREPARER (OPTIONAL): REGULATORY DEPT.

- SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS -

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY, COMMON NAME(S)	CAS NO.	OSHA PEL	ACGIH-TLV	OTHER LIMITS RECO- MMENDED	do
ACETONE 67-64-1	TWA 750 1	PPM TWA 750	PPM NO DATA	50-60	
ETHANOL 64-17-5	TWA 1000	PPM TWA 1000	PPM NO DATA	20-30	
ISOBUTANE	75-28-5	IWA 800 PPM	TWA 800 PPM	NO DATA	10-20
PROPANE 74-98-6	TWA 1000	PPM TWA 1000	PPM NO DATA	1-5	
N-PROPYL ACETATE	109-60-4	IWA 200 PPM	TWA 200 PPM	NO DATA	1-5
ISOPROPANOL	67-63-0	IWA 400 PPM	TWA 400 PPM	NO DATA	1-5

EMERGENCY OVERVIEW - CLEAR THIN VISCOSITY LIQUID WITH SWEET SOLVENT ODOR.

LANGER: FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. KEEP AWAY FROM HEAT SPARKS AND FLAMES. USE ONLY WITH ADEQUATE VENTILATION. HARMFUL IF SWALLOWED DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

- SECTION 3 HAZARDS IDENTIFICATION -

POTENTIAL HEALTH EFFECTS:

EYES: LIQUID IS MODERATELY IRRITATING TO THE EYES.

SKIN: LIQUID IS MILDLY IRRITATING TO THE SKIN.

INGESTION: INGESTION OF LIGHTD MAY CAUSE VOMITING.

INHALATION: HIGH CONCENTRATION OF VAPORS MAY PRODUCE IRRITATION OF THE RESPIRATORY TRACT, HEADACHE, DIZZINESS, AND NAUSEA.

CHRONIC HEALTH EFFECTS:

CHAUNTE HEALTH EFFECTS:
PROLONGED OR REPPARTED CONTACT MAY CAUSE SKIN SENSITIZATION OR DERMATITIS.
REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED COCUPATIONAL OVEREXPOSURE TO
SOLVENIS WITH IRREVERSIBLE BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL
MISUSE BY DELIBERATELY CONCENTRATING OR INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

- SECTION 4 FIRST AID MEASURES -

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:
REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION IMMEDIATELY.

EVES .

SKIN: FLUSH SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES.

IF LARGE QUANTITIES OF THIS MATERIAL ARE SWALLOWED, GET IMMEDIATE MEDICAL

- SECTION 5 FIRE FIGHTING MEASURES -

USA FLAME PROJECTION TEST (ASTM D-3065): >18", FLASHBACK; FLAMMABLE

FLAMMABLE LIMITS:

EXTINGUISHING MEDIA: USE ALCOHOL FOAM, DRY CHEMICAL OR CO2. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.

SPECIAL FIRE FIGHTING PROCEDURES:
WATER MAY BE INEFFECTIVE, WATER MAY BE USED TO KEEP FIRE-EXPOSED CONTAINERS
COOL UNTIL FIRE IS OUT. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS
OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. DO
NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE
SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE
PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSICN HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND, OR BE MOVED BY VENTILATION AND BE IGNITED BY IGNITION SOURCE.

- SECTION 6 ACCIDENTAL RELEASE MEASURES -

SMALL SPILL: ABSORB LIQUID WITH NON-COMBUSTIBLE FLOOR ABSORBENT AND PLACE IN NON-LEAKING CONTAINER; SEAL PROPERLY AND DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

LARGE SPILL:
EVACUATE AREA OF UNPROTECTED PERSONNEL. ELIMINATE ALL IGNITION SOURCES. STOP SPILL AT SOURCE IF SAFE TO DO SO. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. PREVENT SPILL FROM ENTERING DRAINS, SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES. PUMP OR VACUUM TRANSFER SPILLED PRODUCT TO CLEAN CONTAINERS FOR RECOVERY. ABSORB UNRECOVERABLE PRODUCT. TRANSFER CONTAMINATED ABSORBENT, SOIL AND OTHER MATERIALS TO CONTAINERS FOR DISPOSAL. DISPOSE OF PROPERLY IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

- SECTION 7 HANDLING AND STORAGE -

HANDLING:
EMPTY CONTAINERS RETAIN RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS.
DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH
CONTAINERS TO HEAT, SPARKS, FLAMES, STATIC ELECTRICITY, OR OTHER SOURCES OF
IGNITION. MANY HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUCEPTIBLE TO
SUDDEN SCONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT
TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR
IGNITION TEMPERATURES. IGNITION TEMPERATURES DECREASE WITH INCREASING VAPOR
VOLUME AND VAPOR VOLUME AND VAPOR/AIR CONTACT TIME, AND ARE INFLUENCED BY
PRESSURE CHANGES. IGNITION OF ORGANIC CHEMICAL VAPORS MAY OCCUR AT TYPICAL
ELEVATED-TEMPERATURE PROCESS CONDITIONS, ESPECIALLY IN PROCESSES OPERATING
UNDER YACULUM IF SUBJECTED TO SUDDEN INGRESS OF AIR, OR OUTSIDE PROCESS
EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPORS OR
MISTS TO THE ATMOSPHERE OCCURS. ANY PROPOSED USE OF THIS PRODUCT IN
ELEVATED-TEMPERATURE PROCESSES SHOULD BE THOROUGHLY EVALUATED TO ASSURE THAT
SAFE OPERATING CONDITIONS ARE ESTABLISHED AND MAINTAINED.

STORAGE:

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. STORE IN COOL, WELL-VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIALS. ALL 5 GALLON PAILS AND LARGER METAL CONTAINERS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION —

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT USUALLY NECESSARY. USE WITH ADEQUATE VENTILATION, USE NIOSH/MSHA APPROVED RESPIRATOR IF PELS OR TLVS ARE EXCEEDED.

ENGINEERING CONTROLS: LOCAL EXHAUST: NOT USUALLY NEEDED MECHANICAL (GENERAL): YES SPECIAL: NONE

OTHER: NONE

PROTECTIVE GLOVES: CHEMICAL RESISTANT GLOVES IF SKIN CONTACT IS POSSIBLE (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER).

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS. WEAR CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATION IF SPLASHING IS POSSIBLE.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NOT USUALLY NECESSARY. FOR BULK MATERIAL, IF DIRECT CONTACT IS POSSIBLE, WEAR APRON, BOOTS, FACE SHIELD, ETC. AS NEEDED.

WORK/HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS. WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, SMOKING, USING RESTROOMS, ETC.

- SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES -

BOILING POINT: 133 DEG. F

SPECIFIC GRAVITY (H2O = 1) @ 70 DEG. F: 0.79

VAPOR PRESSURE (MM-HG @ 70 DEG. F): NO DATA

MELTING POINT: NO DATA

VAPOR DENSITY (AIR = 1): GREATER THAN ONE (1)

EVAPORATION RATE (BUTYL ACETATE = 1): GREATER THAN ONE (1)

SOLUBILITY IN WATER: SOLUBLE

pH: NO DATA

APPEARANCE AND ODOR: CLEAR THIN VISCOSITY LIQUID WITH SWEET SOLVENT ODOR.

VOC: THIS PRODUCT CONTAINS 388 GRAMS PER LITER OR 48.98% BY WEIGHT VOC'S.

- SECTION 10 STABILITY AND REACTIVITY -

CHEMICAL STABILITY: UNSTABLE () STABLE (X)

CONDITIONS TO AVOID - NONE KNOWN

INCOMPATIBILITY (MATERIALS TO AVDID):
STRONG OXIDIZING AND REDUCING AGENTS, STRONG ALKALIES AND STRONG ACIDS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, SOOT AND VARIOUS ORGANIC OXIDATION BY-PRODUCTS.

HAZARDOUS POLYMERIZATION:
MAY OCCUR ()
WILL NOT OCCUR (X)

CONDITIONS TO AVOID: NO DATA

- SECTION 11 TOXICOLOGICAL INFORMATION -

ORAL LD50 (RAT) DERMAL LD50 (RABBIT) INHALATION LC50 (RAT)

ACETONE 8.5 - 10.70 G/KG 20 G/KG

NO DATA

PLEASE REFER TO SECTION 3 FOR AVAILABLE INFORMATION ON POTENTIAL HEALTH

- SECTION 12 ECOLOGICAL INFORMATION

NO SPECIFIC ECOLOGICAL DATA ARE AVAILABLE FOR THIS PRODUCT. PLEASE REFER TO SECTION 6 FOR INFORMATION REGARDING ACCIDENTAL RELEASES AND SECTION 15 FOR REGULATORY REPORTING INFORMATION.

- SECTION 13 DISPOSAL CONSIDERATIONS -

DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

- SECTION 14 TRANSPORT INFORMATION -

(NOT MEANT TO BE ALL INCLUSIVE)

DOMESTIC HIGHWAY (CONTAINERS <1 QUART ARE ORM-D):
PROPER SHIPPING NAME: NO DATA
HAZARD CLASS/SUBSIDIARY HAZARD: CONSUMER COMMODITY, ORM-D
UN/NA NO.: NO DATA
PACKING GROUP: NO DATA
LABEL REQUIRED: NO DATA

DOMESTIC AIR SHIPMENTS: VARIES PROPER SHIPPING NAME: NO DATA HAZARD CLASS/SUBSIDIARY HAZARD: NO DATA UN/NA NO.: NO DATA PACKING GROUP: NO DATA LABEL REQUIRED: NO DATA

- SECTION 15 REGULATORY INFORMATION -

(NOT MEANT TO BE ALL INCLUSIVE - SELECTED REGULATIONS REPRESENTED)

U.S. FEDERAL REGULATIONS:

CARCINOGENICITY:

NTP?

IARC MONOGRAPHS?

OSHA REGULATED?

OSHA:

HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

THIS PRODUCT DOES NOT CONTAIN INGREDIENTS WHICH ARE LISTED AND MAY REQUIRE REPORTING UNDER SARA TITLE III SEC. 313 IF USED OVER THE THRESHOLD REPORTING QUANTITY. THIS INFORMATION MUST BE INCLUDED IN ALL MSDSS THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

CALIFORNIA PROPOSITION 65: THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY MATERIAL LISTED UNDER CALIFORNIA'S PROPOSITION 65.

- SECTION 16 OTHER INFORMATION -

MSDS STATUS: REVISED SECTION(S):

WARNING!
THE USE OF THIS PRODUCT IS BEYOND THE CONTROL OF THE MANUFACTURER AND DISTRIBUTOR; THEREFORE, NO GUARANTEE, EXPRESSED OR IMPLIED, IS MADE AS TO THE EFFECTS OF SUCH OR THE RESULTS TO BE OBTAINED IF NOT USED IN ACCORDANCE WITH DIRECTIONS OR ESTABLISHED SAFE PRACTICE. THE USER MUST ASSUME ALL RESPONSIBILITY, INCLUDING INJURY OR DAMAGE, RESULTING FROM ITS MISUSE AS

SUCH, OR IN COMBINATION WITH OTHER MATERIALS. THE MANUFACTURER AND DISTRIBUTOR WARRANT ONLY THAT THIS PRODUCT MEETS THE SPECIFICATIONS FOR SUCH PRODUCT. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER OF THIS PRODUCT. THE MANUFACTURER AND DISTRIBUTOR SHALL BE IN NO WAY RESPONSIBLE FOR THE PROPER USE OF THIS PRODUCT. THE SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER AND DISTRIBUTOR FOR BREACH OF WARRANTY SHALL BE REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT IN THE EVENT THAT A DEFECTIVE CONDITION OF THE PRODUCT SHALL BE FOUND TO EXIST. NO OTHER REMEDY (INCLUDING BUT NOT LIMITED TO INCIDENTAL OR CONSEQUENTIAL DAWAGES FOR INJURY TO PERSON OR PROPERTY OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE.

FORMULA: 8947A