

CORONADO PAINT COMPANY,INC -- RUST SCAT ENAMEL,TINT BASE (FORMULA 31-33) -- 8010-00N006484

=====  
Product Identification  
=====

Product ID:RUST SCAT ENAMEL,TINT BASE (FORMULA 31-33)  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00N006484  
MSDS Number: BCMWS  
=== Responsible Party ===  
Company Name:CORONADO PAINT COMPANY,INC  
Address:308 OLD COUNTY RD  
Box:308  
City:EDGEWATER  
State:FL  
ZIP:32032-1812  
Country:US  
CAGE:33200

=== Contractor Identification ===  
Company Name:CORONADO PAINT COMPANY, INC.  
Address:308 OLD COUNTY ROAD  
Box:City:EDGEWATER  
State:FL  
ZIP:32132-1812  
Country:US  
Phone:904-428-6461  
CAGE:33200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS (ACCORDING TO MANUFACTURER,PRESENT NO HAZARD)  
Fraction by Wt: 30.6%

Ingred Name:VEHICLE (ACCORDING TO MANUFACTURER,PRESENTS NO HAZARD)  
Fraction by Wt: 32.3%

Ingred Name:ALIPHATIC HYDROCARBONS (SOLVENTS)  
Fraction by Wt: 37.1%  
ACGIH TLV:500 PPM (MFR)

=====  
Hazards Identification  
=====

Effects of Overexposure:PRODUCES SEVERE EYE IRRITATION,DRYING OF SKIN.  
EXCESSIVE INHALATION CAUSES HEADACHE,DIZZINESS,NAUSEA

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/H\*20 FOR AT LEAST 15 MIN. SKIN: WASH W/MILD  
SOAP & H\*20 & APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR &  
CALL A PHYSICIAN. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

=====  
Fire Fighting Measures  
=====

Flash Point:104F (SETA)  
Lower Limits:1.1  
Upper Limits:6.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2  
Fire Fighting Procedures:H\*20 NOT ORDINARILY EFFECTIVE. SCATTERS LIQ &  
SPREADS FIRE.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES W/AIR.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:WEAR A NIOSH/MSHA APPROVED RESPIRATOR. FLUSH  
W/H\*20 INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO  
SPARKS,FIRE OR HOT METAL SURFACES.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,OPEN FLAME.  
USE W/ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN  
CONTACT.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD SELF CONTAINED RESPIRATOR IF  
TLV IS EXCEEDED.  
Ventilation:LOCAL EXHAUST  
Protective Gloves:YES  
Eye Protection:YES  
Other Protective Equipment:EYE BATH & SAFETY SHOWER  
Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F  
Vapor Pres:2  
Vapor Density:>1  
Spec Gravity:1.162  
Evaporation Rate & Reference:<1 (BU AC)  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:WHITE OPAQUE LIQUID,MINERAL SPIRITS ODOR  
Percent Volatiles by Volume:56.8

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Stability Condition to Avoid:EXCESSIVE HEAT,SPARKS,OPEN FLAMES  
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON  
MONOXIDE

=====  
===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL,INCINERATION UNDER SAFE & SUPERVISED  
CONDITIONS. WASTE DISPOSAL MUST BE IAW FEDERAL,STATE & LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.