

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** STA'-PUT S145 Contact Adhesive (item #S145-01C)

#### MANUFACTURER

ITW TACC  
 56 Air Station Industrial Park  
 Rockland MA 02370

**Product Stewardship:** (781) 878-7015

**Service Number:** (800) 503-6991

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** STA'-PUT is a registered trademark of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

#### HAZARD DESIGNATION

"F" - Highly flammable

"Xn" - Harmful

#### EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** DANGER! Extremely flammable liquid and vapor. Vapor may cause flash fire and explosion. Harmful or fatal if swallowed. Harmful if absorbed through the skin. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. High vapor concentrations may cause drowsiness. Can cause eye, skin and respiratory tract irritation.

#### POTENTIAL HEALTH EFFECTS

**EYES:** Can cause severe eye irritation and corneal damage.

**SKIN:** Causes defatting and skin irritation. Can cause dermatitis.

**SKIN ABSORPTION:** May be absorbed through the skin in harmful amounts.

**INGESTION:** Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Harmful or fatal if swallowed.

**INHALATION:** May cause nose or throat irritation. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

**SKIN:** Mild to moderate skin irritant.

**SKIN ABSORPTION:** May be absorbed through the skin and can contribute to overall exposure. Effects are similar to CNS depression.

**INGESTION:** May result in central nervous system (CNS) depression with symptoms such as headaches, nausea, vomiting, diarrhea, dizziness, incoordination and unconsciousness. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

**INHALATION:** High vapor concentrations may cause CNS depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation,

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

reduced appetite, confusion, and unconsciousness.

**ACUTE TOXICITY:** High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion and unconsciousness.

**CHRONIC EFFECTS:** Damage to the nervous system of the extremities, peripheral neuropathy, with symptoms including numbness, tingling and weakness in the toes and fingers, sensory impairment to touch, pain, vibration and temperature, muscular weakness, blurred vision, coldness of extremities, loss of body weight and reflexes, and even paralysis. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

**MUTAGENICITY:** None known.

**ROUTES OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, and Skin Contact

**TARGET ORGAN STATEMENT:** Central Nervous System (CNS)

**IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name       | Wt.%    | CAS         | EINECS    | Classification  |
|---------------------|---------|-------------|-----------|-----------------|
| VM&P Naptha         | 25 - 50 | 008032-32-4 | 232-453-7 | F, Xn; 11-65    |
| Toluene             | 15 - 40 | 000108-88-3 | 203-625-9 | F, Xn; 11-20    |
| Methyl Ethyl Ketone | 10 - 30 | 000078-93-3 | 201-159-0 | F, Xi; 11-36/37 |

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

**INGESTION:** Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** (33°F) Setaflash CC Tester-ASTM D 3828

**FLAMMABLE LIMITS:** 0.9 to 10.0

**AUTOIGNITION TEMPERATURE:** (450°F) to (997°F)

**FLAMMABLE CLASS:** Class IB

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
MSDS No: R 3113A  
Date Revised: 11/13/2009  
Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

**GENERAL HAZARD:** Flammable liquid and vapor.

**EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide, water spray or fog.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Aldehydes

**EXPLOSION HAZARDS:** Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

**SENSITIVE TO STATIC DISCHARGE:** Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

**SENSITIVITY TO IMPACT:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
MSDS No: R 3113A  
Date Revised: 11/13/2009  
Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

**HANDLING:** Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

**STORAGE:** Keep container closed when not in use. Store in a dry well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

**STORAGE TEMPERATURE:** 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

**SHELF LIFE:** 1 year from manufacture date

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### EXPOSURE GUIDELINES

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)               |      |                 |                       |           |                        |
|---|------|-----------------|-----------------------|-----------|------------------------|
|   |      | EXPOSURE LIMITS |                       |           |                        |
|   |      | OSHA PEL        |                       | ACGIH TLV |                        |
| Chemical Name   |      | ppm             | mg/m <sup>3</sup>     | ppm       | mg/m <sup>3</sup>      |
| VM&P Naptha   | TWA  | NL [1]          | NL [1]                | 300 ppm   | 1370 mg/m <sup>3</sup> |
|   | STEL | NL [1]          | NL [1]                | NL [1]    | NL [1]                 |
| Toluene   | TWA  | 200 ppm         | NL                    | 20 ppm    | NL                     |
|   | STEL | 300 ppm [2]     | NL [2]                | NL [1]    | NL [1]                 |
| Methyl Ethyl Ketone                                       | TWA  | 200 ppm         | 590 mg/m <sup>3</sup> | 200 ppm   | 590 mg/m <sup>3</sup>  |
|   | STEL | NL [1]          | NL [1]                | 300 ppm   | 885 mg/m <sup>3</sup>  |
| <b>Footnotes:</b><br>1. NL = Not Listed<br>2. C = Ceiling |      |                 |                       |           |                        |

**ENGINEERING CONTROLS:** Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) or a full face respirator.

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**PROTECTIVE CLOTHING:** Wear chemical resistant gloves, such as nitrile rubber.

**WORK HYGIENIC PRACTICES:** Wash hands thoroughly after use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Solvent-like

**COLOR:** Clear

**PERCENT VOLATILE:** 79.1

**Notes:** by weight

**BOILING POINT:** 79.6°C (175.3°F) to 110.6°C (231°F)

**FLASHPOINT AND METHOD:** (33°F) Setaflash CC Tester-ASTM D 3828

**SOLUBILITY IN WATER:** Slight

**EVAPORATION RATE:** > 1.0 (n-Butyl Acetate=1)

**DENSITY:** 7.15 lbs/gal

**SPECIFIC GRAVITY:** 0.858

**(VOC):** 678.100 gr/L EPA Method 24 VOC

**Notes:** Photochemically Reactive Only VOC: 677.3 gr/L

**COMMENTS:** 1.94 lb VHAP/lb Solid  
 40.6% by weight HAP

### 10. STABILITY AND REACTIVITY

**STABLE:** Yes

**HAZARDOUS POLYMERIZATION:** No

**STABILITY:** Stable.

**POLYMERIZATION:** Product will not undergo polymerization.

**CONDITIONS TO AVOID:** Avoid fire, sparks, static electricity and hot surfaces.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and carbon dioxide may form when heated to decomposition.

**INCOMPATIBLE MATERIALS:** Strong oxidizing agents, strong acids and strong bases.

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE

| Chemical Name       | ORAL LD <sub>50</sub> (rat) | DERMAL LD <sub>50</sub> (rabbit) | INHALATION LC <sub>50</sub> (rat) |
|---------------------|-----------------------------|----------------------------------|-----------------------------------|
| VM&P Naptha         | No data                     | No data                          | No data                           |
| Toluene             | No data                     | No data                          | No data                           |
| Methyl Ethyl Ketone | 2737 mg/kg                  | 5000 to 13000 mg/kg              | 23500 mg/L (8-hr dose)            |

#### CARCINOGENICITY

| Chemical Name | IARC Status |
|---------------|-------------|
| Toluene       | 3           |

**IRRITATION:** Eyes, nose, throat, respiratory tract irritation.

**CORROSIVITY:** Not Applicable

**SENSITIZATION:** Not Applicable

**NEUROTOXICITY:** Not Applicable

**GENETIC EFFECTS:** Not Applicable

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

**BIOACCUMULATION/ACCUMULATION:** Contains components with the potential to bio-accumulate.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Adhesives

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1133

**PACKING GROUP:** II

**NAERG:** 128

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

**MARINE POLLUTANT #1:** None

**OTHER SHIPPING INFORMATION:** contains (Toluene, Methyl Ethyl Ketone)

**SPECIAL SHIPPING NOTES:** If individual container size is less than 1.3 gallons, the proper shipping name is:

ORM-D Consumer Commodity  
 Non-Regulated

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable Liquid  
 \*\* for containers > 1.3 gallons (4.9 Liters) \*\*

##### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

##### EPCRA SECTION 313 SUPPLIER NOTIFICATION

| Chemical Name       | Wt.%    | CAS         |
|---------------------|---------|-------------|
| Toluene             | 15 - 40 | 000108-88-3 |
| Methyl Ethyl Ketone | 10 - 30 | 000078-93-3 |

##### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

| Chemical Name       | Wt.%    | CERCLA RQ  |
|---------------------|---------|------------|
| Toluene             | 15 - 40 | 1,000 lbs. |
| Methyl Ethyl Ketone | 10 - 30 | 5,000      |

##### TSCA (TOXIC SUBSTANCE CONTROL ACT)

| Chemical Name       | CAS         |
|---------------------|-------------|
| VM&P Naptha         | 008032-32-4 |
| Toluene             | 000108-88-3 |
| Methyl Ethyl Ketone | 000078-93-3 |

##### CLEAN AIR ACT

| Chemical Name       | Wt.%    | CAS         |
|---------------------|---------|-------------|
| Toluene             | 15 - 40 | 000108-88-3 |
| Methyl Ethyl Ketone | 10 - 30 | 000078-93-3 |

# MATERIAL SAFETY DATA SHEET



Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

### STATES WITH SPECIAL REQUIREMENTS

| Chemical Name       | Requirements   |
|---------------------|--|
| Toluene             | New Jersey Right to Know List<br>Pennsylvania Right to Know List<br>Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical |
| Methyl Ethyl Ketone | New Jersey Right to Know List<br>Pennsylvania Right to Know List<br>Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical |

**CALIFORNIA PROPOSITION 65:** This product contains toluene, a chemical known to the state of California to cause birth defects or other reproductive harm.

| Chemical Name | Wt. %   | Listed                   |
|---------------|---------|--------------------------|
| Toluene       | 15 - 40 | • Developmental Toxicity |

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable Liquid



Toxic

### EUROPEAN COMMUNITY

#### EEC LABEL SYMBOL AND CLASSIFICATION



"F" - Highly flammable



"Xn" - Harmful

### 16. OTHER INFORMATION

**INFORMATION CONTACT:** (781) 878-7015

**REVISION SUMMARY:** Revision #: 7 This MSDS replaces the November 13, 2009 MSDS. Any changes in information are as follows: In Section 1 Comments



# MATERIAL SAFETY DATA SHEET




Date Issued: 11/13/2009  
 MSDS No: R 3113A  
 Date Revised: 11/13/2009  
 Revision No: 7

## STA'-PUT S145 Contact Adhesive (item #S145-01C)

### HMIS RATING

|                             |          |          |
|-----------------------------|----------|----------|
| <b>HEALTH:</b>              | *        | <b>2</b> |
| <b>FLAMMABILITY:</b>        |          | <b>3</b> |
| <b>PHYSICAL HAZARD:</b>     |          | <b>0</b> |
| <b>PERSONAL PROTECTION:</b> | <b>B</b> |          |

### NFPA CODES



### GENERAL STATEMENTS: Keep out of reach of children

For professional or industrial use only

If you cannot read, or do not understand all directions, cautions, and warnings, do not use this product

For spray applications, use only with approved equipment

### MANUFACTURER DISCLAIMER:

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW TACC. The data on this sheet relates only to the specific material designated herein. ITW TACC assumes no legal responsibility for use or reliance upon these data.